49 AIR165-2750



| 型号 Type | | AIR165-2750 |
|------------------------------|--|---|
| 轴数 Axes | | 6 |
| 负载 Payload | | 165kg |
| 机器人本体 Manipulator | 重量 Weight | 1200kg |
| | 最大运动范围 Reach | 2750mm |
| 定位精度 Positioning accuracy | 位置重复定位精度 Position repeatability | ±0.1mm |
| IP 等级 Ingress Protection | | IP54 (小臂: IP67) IP54 (Forearm: IP67) |
| 安装方式 Mounting | | 地装 Floor |
| 运动范围 Working range | 轴 1* Axis 1 rotation | -170°/+170° |
| | 轴 2 Axis 2 arm | -60°/+85° |
| | 轴 3 Axis 3 arm | -120°/+155° |
| | 轴 4 Axis 4 wrist | -360°/+360° |
| | 轴 5 Axis 5 bend | -125°/+125° |
| | 轴 6 Axis 6 turn | -360°/+360° |
| 运动速度 Rotation rate | 轴 1 Axis 1 rotation | 125°/s |
| | 轴 2 Axis 2 arm | 113°/s |
| | 轴 3 Axis 3 arm | 125°/s |
| | 轴 4 Axis 4 wrist | 180°/s |
| | 轴 5 Axis 5 bend | 175°/s |
| | 轴 6 Axis 6 turn | 280°/s |
| 适用控制柜 Controllers | | ARC4-165 |
| 安装条件 Mounting conditions | 环境温度: 0~45℃ Ambient temperature: 0~45℃ 湿度: 恒温下 95% 以内,无凝露。 Humidity: not more than 95% at constant temperature without condensation. 允许高度: 操作机正常工作环境的海拔高度不应超过 1000 米(在 1000 米 -4000 米高度范围内,操作机应降额使用)。 Allowable altitude: not more than 1000m above sea level. 不应有腐蚀性、可燃性、易爆性气体。 No corrosive, flammable or explosive gases. | |

^{*} 若去除机械限位, 运动范围可达 -180°/+180°。 If the mechanical limit is removed, the working range can reach -180°/+180°.

AIR165-2750

高速度 高精度 高稳定性 汽车行业点焊能手 纤细的手腕 High speed
High precision
High stability
Spot welding manipulator
Slim wrist

■ 具有连续点焊短距离快速移位能力, 0.5s 内可完成 50mm 位移的快速运动。


AIR165-2750 is capable of rapid movement over a short distance while continuous spot welding, achieving 50mm displacement within 0.5s.

- 操作机手腕纤细,非常适于探入到白车身内进行点焊作业。 AIR165-2750 has a slim wrist which is very suitable for spot welding in the body in white.
- 配备了管线包,使得焊接线缆、软管(水/气)与机器人本体紧密贴合,有效减少干扰和线缆磨损及喷溅损坏,十分适于复杂度较高的汽车点焊作业。

AIR165-2750 is equipped with dress package, which makes the welding cable and hose (water/gas) closely attached to the robot body, effectively reduces interference, cable wear and splashing damage, very suitable for automobile spot welding with high complexity.



外形尺寸及运动范围 Outline dimension and Working range



法兰图 Flange drawing

底座安装图 Base installation drawing

